


LED1200 Framing Shutter Moving Head Light-4in1

TV-LED1200

TV-LED1200H / TV-LED1200W

FRAMING LIGHTS



► OPTICAL SYSTEM

- Power Supply: 100-240V, 50/60Hz
- Power: 1420W (220V), power factor: PF ≥0.98
- Light source: 1200W LED module (lifespan: ≥20000h)
- Color temperature: 6700K
- CRI: TV-LED1200: 70+, TV-LED1200H: 95+

► MAIN FEATURE

- Linear CMY color mixing
- Linear CTO(6700K-3200K)
- Fixed color wheel with 5 dichroic colors +White
- 1 fixed gobo wheel with 8 gobos + Open
- 1 rotating gobo wheel with 6 replaceable gobos + Open
- 1 effect wheel
- Prism: Rotating 4-facet circular prism
- Frost filters: 2 separate, variable frost filters (light and medium)
- Electronic Dimming: 0-100%
- Iris: Motorized iris
- Framing: 4 blades move separately with +/- 60°rotation of the full system smooth, flexible blade movements at variable speed
- Zoom: 5.5°-50°
- Pan/Tilt: 540/270°, 16 bit precision scanning; Pan & Tilt lock
- Strobe: 1-25 times/sec
- Noise Mode: Auto Mode, Theater Mode, Silent Mode

► OPERATING

- Protection level: IP20
- Working Environment: -10C°- 45C°

► CONTROL

- DMXchannel: 37/50 CH
- Art-net Ethernet control protocol, SACN protocol, RDM compatible
- Signal input/output: 5pins & 3pins XLR, RJ45 interface
- Power: PowerCON TRUE1 Power input

► MEASUREMENT

- Product Size: 870*467*309mm
- Net weight: 46kg

